

# MONITOR MOUNTS

## SUPPORTI MONITOR

cod.  
**05806**

### FLAT PANEL TV WALL BRACKET, FIX, GREY

Supporto universale per monitor da parete, fisso, grigio

Net weight   <i>Peso netto</i>	9,00 kg
Closed length   <i>Ingombro</i>	< 40 mm
Max load   <i>Carico Max</i>	60 kg
Thickness   <i>Spessore</i>	1,5/2 mm Tubes - Tubi
Max Monitor Size   <i>Dim. mass. monitor</i>	42" - 55"
Materials   <i>Materiali</i>	Fe
Treatments   <i>Trattamenti</i>	Grey - Grigio

Fix Universal Plasma wall bracket, in steel plate. The bracket is composed of two plates: the first is to be fixed to the wall (365x605mm) and the other to the monitor (850x590 mm). It is compatible with all models and brands of plasma (from 42" to 55") thanks to the "sliding buttonholes system" that cover a horizontal 284-700 mm distance and a 80-475 mm vertical one. Thanks to that system after you have fixed the plasma you can centre it to hide the wall plate. The equipment includes 6 "jolly plates" with the hole for M5-M6-M8-M10 screws that centre the fixing screw to the plasma. The PVC insert grants the isolation of the bracket from the plasma. In the inferior part two security screws have been inserted to avoid attempts of stealing the plasma. Within the equipment 6 M5-M6-M8-M10 screws are also supplied. The time to assemble the plasma to the wall is 5 minutes.

*Supporto Plasma fisso da parete "universal", realizzato in lamiera d'acciaio. Il supporto è composto da due piastre: la prima da fissare a parete (365x605mm), e l'altra da fissare al monitor (850x590m). La compatibilità con tutti i modelli e marche di plasma (da 42" a 55") è garantita dal "sistema ad asole scorrevoli" che coprono un interasse orizzontale 284-700mm. e verticale 80-475mm. Grazie a tale sistema una volta fissato il plasma, lo si può centrare per evitare che la piastra a parete sia visibile. In dotazione vengono forniti 6 piastrini "jolly" con foro per viti M5-M6-M8-M10 che agiscono come centratura della vite di fissaggio con il plasma. Il distanziale in PVC garantisce l'isolamento del supporto rispetto al plasma. Nella parte inferiore sono state inserite due viti di sicurezza per scoraggiare tentativi di furto del plasma stesso. In dotazione vengono fornite anche 6 viti M5-M6-M8-M10. Tempo di montaggio del plasma a parete: 5 minuti.*



cod.  
**10557**

### FLAT PANEL TV WALL BRACKET, FIX, ANTHRACITE

Supporto universale per monitor da parete, fisso, antracite satinato

