

PENDANT LOUDSPEAKER (360° DISPERSION) LTS.SP3860B



The SP3860B is a pendant speaker built-in 70V / 100V transformer. The 70V / 100V transformer technique reduces line losses on longer distance and allows easy parallel connection of multiple loudspeakers. The built-in 6" full range speaker driver is designed of wide frequency response 100-10 kHz, the multiple power taps of 7.5W, 10W, 15W, 20W, 30W & 60W could meet different applications varies from room size and ambient noise surroundings.

The ABS enclosure is of black color. Easy and secure wall mount installation through the supplied secured steel mounting ring kit. It is ideal choice for industrial and commercial applications in the outdoor area of train station, hopping mall, parking area and factory where background music and paging is needed.

Specifications

Power taps 100V	7,5W, 10W, 15W, 20W, 30W, 60W
Power taps 70V	3,75W, 5W, 7,5W, 10W, 15W, 30W
Impedance	White : 1.3 KΩ, red : 1 KΩ, yellow : 670Ω, brown : 500Ω, blue : 330Ω, green : 165Ω, black : Com
SPL(1W/1M)	102 dB
Max. SPL (rated W/1M)	120 dB
Frequency response (-10 dB)	100 – 13 kHz
Finish	Baffle : Black ABS
Speaker driver	13 x 1 cm
Dimensions	385 x 385 x 302 mm
Weight	3,4 kg
Mounting	Hook

