

5" 6W PENDANT SPEAKER LTS.SP206



The SP206 is a pendant speaker built-in 70V / 100V transformer. The 70V / 100V transformer technique reduces line losses on longer distance and allows easy parallel connection of multiple loudspeakers. The built-in 5" full range speaker driver is designed of wide frequency response 130 - 14 kHz, the various power output 1.5W, 3W & 6W could meet different applications varies from room size and ambient noise surroundings.

The ABS enclosure and speaker cable tail are of white color. Easy and secure wall mount installation to be suspended on the roof the hotel lobby or super market's case desk. It is ideal choice for industrial and commercial applications for hotel, super market, exhibition center, shopping mall, where background music and paging is needed.

Specifications

Power taps 100V	1,5W, 3W, 6W
Power taps 70V	0,75W, 1,5W, 3W
Impedance	Blue : Com, red : 6.7 K Ω , green : 3.3 K Ω , yellow : 1.7 K Ω
SPL (1W/1M)	91 dB \pm 3 dB
Max. SPL (rated W/1M)	99 dB
Frequency response (-10dB)	130 – 14 kHz
Finish	Baffle & grille : White ABS
Speaker driver	13 x 1 cm
Dimensions	205 x 205 mm
Weight	1,1 kg
Mounting	With mounting bracket fixed by screw

