

9X8W LED PROJECTOR LTL.PL9825IP Operation manual



TABLE OF CONTENTS

1. About this product.....	Page 3
2. Operation instructions.....	Page 3
3. DMX modes.....	Page 4
4. Remote functions.....	Page 5
5. Specifications.....	Page 5

1. ABOUT THIS PRODUCT

Thank you for choosing a product from the LINEARLEDS range. The PL9825IP is a projector LED PAR, IP 65, equipped with 9 LED of 8W each. Thanks to the RGBW LEDs 4 in 1 ultra bright, this projector is able to combine more than 16.7 millions color effects. The PL9825IP is perfectly adapted for stage and architectural lighting.

2. OPERATION INSTRUCTIONS

- Setting solid colors and integrated programs :

When the screen displays :

01.STATIC
R00G00B00W00 F00

You can adjust the brightness of the 4 colors and, via F00, adjust the flash speed.

Press ENTER, when the display flashes, select the integrated program with keys UP / DOWN

02. CHANGE-15 (15 colors)
SP01-99 F00-99

03.CHANGE-4 (4 colors)
SP01-99 F00-99

04. DREAM (15 colors)
SP01-99 F00-99

- Master / slave setting mode : S L A V E
 M O D E

- DMX protocol :

Press the MODE button until the display shows

DMX MODE
ADDR : 001
CH : 006

Then set the desired address via the UP / DOWN, but also the number of desired channels (4 - 6 or 7 channels)

3. DMX MODES

6 channels mode

Channel	Value	Function
1	000-255	Red (0-100%)
2	000-255	Green (0-100%)
3	000-255	Blue (0-100%)
4	000-255	White (0-100%)
5	000-255	Master dimmer (0-100%)
6	000-000	ON
	001-005	OFF
	006-010	ON
	011-255	Strobe (increase)

4 channels mode

Channel	Value	Function
1	000-255	Red (0-100%)
2	000-255	Green (0-100%)
3	000-255	Blue (0-100%)
4	000-255	White (0-100%)

7 channels mode

Channel	Value	Function
1	000-255	Master dimmer (0-100%)
2	000-255	Flash (slow-fast)
3	000-255	Red (0-100%)
4	000-255	Green (0-100%)
5	000-255	Blue (0-100%)
6	000-255	White (0-100%)
7	000-004	ON
	005-125	15 colors change
	006-010	15 colors dream

4. REMOTE FUNCTIONS

BLACKOUT : LED OFF

SPR : Integrated program, «+ -» to select the 3 scenes

FL : Flash ON/OFF, «+ -» to adjust the speed

SP : Speed control, «+ -» to adjust the color changes speed and dream

D : DMX mode

SA : No use

SL : Master/Slave mode

S : Address setting DMX with 0, 1, 2, 3, 4, 5, 6, 7, 8, 9

RGBW : Static color, with «+ -» to adjust the RGBW brightness

5. SPECIFICATIONS

- LED : 9 x 8W, 4 in 1, RGBW
- Beam angle : 25°
- Control DMX : 4 - 6 - 7 channel
- Master / slave mode
- Effects : Strobe, dimmer 0-100%
- Power supply : AC 100 ~ 250V - 50 / 60 Hz
- Electric power : 80W
- Dimensions : 260 x 160 x 260 mm
- Weight : 4 kg

LINEARLEDS



Linear Technologie • 11 rue du Puits Rochefort • 42 100 Saint-Etienne
Tél: +33 (0)4 77 81 49 49 • Fax: +33 (0)4 77 81 49 40 • www.lineartech.fr