

60W AMPLI PREAMPLI LTS.PA860

This ampli - preampli professional range is designed for commercial and industrial sound applications of «Public Address». Reliable, compact et polyvalent, the PA860 is perfect for mobile or fix installations.



This ampli - preampli has 4 outputs (50V - 70V or 4 - 16 Ω), 4 micro inputs with phantom power supply and priorities and 4 double RCA inputs with switchable line.

The PA860 has also a chime 2 or 4 tones, with volume controller and input for remote.

Specifications

Power supply	60W
Inputs	MIC 1, 2, 3, 4 : XLR balanced with phantom power supply. Tape inputs, CD, tuner, line
AUX	RCA unbalanced inputs
Output	On terminal 4 - 16 Ω , 50V, 70V or 100V, balanced line on XLR and broadcast on RCA
Tone	Bass : ± 12 dB @ 100 Hz, treble : ± 12 dB @ 10 kHz
Frequency response	40 Hz ~ 20 kHz (+1 dB, -3 dB)
S/N ratio	> 90 dB
THD + N	<0.1%
Protection	Overload, short circuits and permanent cooling system
Supply	230V / 50 Hz and DC 24V
Power consumption	100W
Dimensions	484 x 393 x 88 mm (19" x 2U)
Weight	10.50 kg