

## 120W AMPLI PREAMPLI LTS.PA8120

This ampli - preampli professional range is designed for commercial and industrial sound applications of «Public Address». Reliable, compact and polyvalent, the PA8120 is perfect for mobile or fix installations.



This ampli - preampli has 4 outputs (50V - 70V ou 4-16  $\Omega$ ), 4 micro inputs with phantom power supply and priorities and 4 double RCA inputs with switchable line. The PA8120 has also a chime 2 or 4 tones, with volume controller and input for remote.

### Specifications

Power supply	120W
Inputs	MIC 1, 2, 3, 4 : XLR balanced with phantom power supply. Tape inputs, CD, tuner, line AUX : RCA unbalanced inputs
Output	On terminal 4-16 $\Omega$ , 50V, 70V or 100V, balanced line on XLR and broadcast on RCA
Tone	Bass : $\pm 12$ dB @ 100Hz, Treble : $\pm 12$ dB @ 10kHz
Frequency response	40Hz ~ 20kHz (+1dB, -3dB)
S/N ratio	> 90dB
THD + N	<0.1%
Protection	Electrical overload, short circuits and permanent cooling system
Supply	230V / 50Hz and DC 24V
Power consumption	200W
Dimensions	484 x 393 x 88 mm (19" x 2U)
Weight	12.50 kg