

AMPLIFIER 240W

LTS.A240L

This amplifier professional range is designed for commercial and industrial sound applications «public address». Reliable, complete and polyvalent the A240L is ideal for fixed and mobile mounting.



This amplifier purposes four 50V, 70V or 100V and 4-16 Ohms outputs. This professional range has a balanced input and output (XLR connectors) and/or unbalanced (jack 6.35 connectors), light indication of states, volume control in front face. The A240L is totally protected against short circuits, electrical overheating, and is equipped with a slaved silent fan.



APPLICATIONS

- Conference rooms,
- Audiovisual presentations,
- Background music system,
 - Resorts,
- Education, sport and recreation centers,
 - Shops,
- Worship places,
- Public spaces,
- Theme parks, ...

Specifications

Power	240W
Output	70V, 100V and 4 - 16 Ω
Input connector	Jack 6.35 mm balanced and XLR3
Output connector	XLR3 balanced
Sensitivity	Input : 775 mV / 10k Ω - Output : 775 mV / 470 Ω
Frequency response	50Hz ~ 16kHz (+1dB, -3dB)
S/N ratio	> 90 dB
THD + N	< 0.1% to 1kHz, 1/3 rated power
Crosstalk	< 50dB
Protection	Overloading, overheating and short circuits
Power supply	~230V / 50Hz
Consumption	400W
Dimensions	484 x 335 x 88 mm (19" x 2U)
Weight	13.20 kg