

CEILING LOUDSPEAKER (POWER 3W-6W-9W) LTS.PL249



The PL249 is a ceiling speaker built-in 70V / 100V transformer. The 70V / 100V transformer technique reduces line losses on longer distance and allows easy parallel connection of multiple loudspeakers.

The built-in 6" speaker driver is designed of wide frequency response 110 - 18 kHz, the multiple power taps 3W, 6W & 9W are helpful for different applications varies from room size and ambient noise surroundings. The aluminium grille and metal baffle are painted in attractive white color. Its spring clip clamp makes the easy and secure installation.

It is ideal choice for industrial and commercial applications in hotel, school, office and factory where background music and paging is needed.

Specifications

Power taps 100V	3 W, 6 W, 9 W
Power taps 70V	1,5 W, 3 W, 4,5 W
Impedance	Black : Com, red : 3.3K Ω , green : 1.7K Ω , white : 1.1K Ω
SPL (1W/1M)	92 dB
Max. SPL (rated W/1M)	106 dB
Frequency response (-10dB)	110 – 18 kHz
Finish	Baffle : White steel / Grille : White steel
Speaker driver	15 cm x 1
Cutout size	220 mm
Dimensions	246 x 70 mm
Weight	1 kg
Mounting	Spring-clip

