

120W AMPLI PREAMPLI LTS.PA7120

This ampli - preampli professional range is designed for commercial and industrial sound applications of «Public Address». Reliable, compact et polyvalent, the PA7120 is perfect for mobile or fix installations, needed an important input sources.



This ampli - preampli has 2 outputs, 1 switchable chime 2 or 4 tones with level controller start by remote or micro desk. This preampli has 5 balanced micro inputs - whose 1 with Voice Over - 2 LINE stereo inputs, 1 dip-switch pad - allow different combination between Line and MIC level - 1 phantom power supply, 1 VCA controller, ...

The input and output levels are adjustable. The PA7120 has also 1 LINE OUT output and 1 input and output for audio processing insertion.

To finish, for security, the PA7120 can be supplied by 24V DC. It is totally protected from short circuits, overheated and has a mechanical ventilation.

This ampli - preampli is designed for background sound and speech microphone applications.

Specifications

Power supply	120W
Output 1	70 - 100V
Output 2	120W under 8Ω
MIC input	Euroblock terminal
Sensitivity / impedance	5mV / 600Ω
LINE input	Euroblock terminal
Inputs AUX1 - AUX2	RCA
Sensitivity / impedance	316mV/10kΩ
LINE output pre OUT balanced	2 RCA
Sensitivity / impedance	1V / 600Ω
Frequency response	50Hz - 20kHz (±2dB)
S/N ratio	> 75dB
THD distorsion	<0.1% @ 1kHz
Tones	Bass : ±10db @ 100Hz; Treble : ±10dB @ 10KHz
Supply	AC 230V / 50Hz
Power consumption	300W
Dimensions	483 x 300 x 88 mm (19" x 2U)
Weight	9.60 kg