

AMPLIFIER 4 X 120W LTS.A4120L

This professional range of amplifier is designed for commercial and industrial sound applications "public address". Reliable, versatile and complete the A4120L is ideal for fixed and mobile applications.



Balanced line inputs by phoenix types 70V, 100V and 4 - 46 ohm speaker outputs for each channel by phoenix types are convenient for installation when selection different speaker matching.

Master volume controls for each control are included. Complete protection includes overheat, overload & short circuit. Indicators for power, signal, peak and protection.

Applications

- Conference rooms,
- Audiovisual presentations,
- Background music systems,
- Resorts and theme parks,
- Educational / sport centers and hobbies,
 - Shops,
- Places of worship,
- Public spaces, ...

Specifications

Rated power output	4 x 120W
Speaker outputs	70V, 100V and 4 - 16 Ω
Input plug	Balanced jack 6.35 mm
Frequency response	50 Hz ~ 16 kHz (+1 dB, -3 dB)
S/N ratio	> 90 dB
THD	< 0.1% at 1 kHz, 1/3 rated power
Crosstalk	< 50 dB
Cooling	Fan automatically start up when temp reached 55 °C
Power supply	~230V / 50 Hz or DC 24V
Power consumption	700W
Dimensions	484 x 335 x 89 mm (19" x 2U)
Weight	26 kg