

## 120W AMPLIFIER

### LTS.A120L

This professional amplifiers range is destined to commercial and industrial applications « public address ». Reliable, complete and polyvalent the A120L is ideal for fixed and mobile use. a silent slaved fan.



This amplifier purpose four outputs 50V, 70V or 100V and 4-16 Ohms. This professional range has one balanced input and output (XLR connectors) and/or unbalanced (jack 6.35 connectors), light indication of states, volume control in front panel. The A120L is totally protect against short circuits, electrical overheating, and is equipped with a silent slaved fan.

#### APPLICATIONS

- Conference rooms,
- Background system sound,
  - Resorts,
- Educational, sports and recreation centers,
  - Shops,
  - Worship places,
  - Public spaces,
  - Theme parks, ...

#### Specifications

|                    |   |
|--------------------|---|
| Power              | 120W  |
| Output             | 70V, 100V and 4 - 16 $\Omega$               |
| Input connectors   | Jack balanced 6.35 mm and XLR3              |
| Output connectors  | XLR3 balanced                               |
| Input sensitivity  | 775 mV / 10k $\Omega$                       |
| Output sensitivity | 775 mV / 470 $\Omega$                       |
| Frequency response | 50 Hz ~ 16 kHz (+1 dB, -3 dB)               |
| S/N ratio          | > 90 dB                                     |
| THD + N            | < 0.1% at 1 kHz, 1/3 rated power            |
| Crosstalk          | < 50 dB                                     |
| Protection         | Overloading, overheating and short-circuits |
| Power supply       | ~ 230V / 50 Hz                              |
| Power consumption  | 200W  |
| Dimensions         | 484 x 335 x 88 mm (19" x 2U)                |
| Weight             | 9.10 kg                                     |