

## 8 CHANNELS INTERPRETATION CONSOLE

### LC3.IRDI08



The IRDI08 is compliant to IEC 60914 international standard. Its display can show conference information and working status in real time. Double interpreters console, two interpreters can translate one by one.

8 channels, multi language interpretation function and monitoring function. Working with channel selector or infrared system to extend the audience.

Removable microphone pole, easy to be transported.

Full digital audio transmission technique. Remote transmission won't influence on sound quality. Adopt full digital audio codec technology and digital audio compression technology. The sound is near CD quality after infrared transmission. Listeners have comfortable, natural and high quality sound finishing.

### Specifications

System capacity	Depends on system controller, 65535 pcs Single controller ≤80 pcs
Frequency response	30 - 20 KHz
Display	128 x 64 LCD display
MIC type	Capacitive
Sensitivity of MIC	-47 Db
SNR	102 Db
Dynamic range	106 Db
Total harmonic distortion	<0.45%
Working power	24 DC,-5%
Working current	50 ma, ±5%
Maximum power	2W
Control type	RS-485
Earphone output	16Ω, 250 mW / 32Ω, 125 Mw
Mount	Big 6 pin DIN
Receiving channels	8
Finish	Aluminium grey , silver
Dimension	375 x 190 x 62 mm